

SAFETY DATA SHEET

A00732 CAROLINA AUTO BRAKE & PARTS 20n14

Version 3.2

Revision Date 04/13/2017

Print Date 07/03/2017

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : A00732 CAROLINA AUTO BRAKE & PARTS 20n14

Material number : 00000000001049127

Manufacturer or supplier's details

Company :

Address :

Telephone :

| | |
|---------------------------------------|---|
| Emergency telephone numbers | |
| For SDS Information | : |
| For a Medical Emergency | : |
| For a Transportation Emergency | : |

Recommended use of the chemical and restrictions on use

Recommended use : Cleaner

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

| | |
|------------|-------------------------------------|
| Appearance | Aerosol containing a compressed gas |
| Colour | clear |
| Odour | solvent-like |

GHS Classification

Flammable aerosols : Category 1
Gases under pressure : Compressed gas
Skin irritation : Category 2
Eye irritation : Category 2A
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

SAFETY DATA SHEET

A00732 CAROLINA AUTO BRAKE & PARTS 20n14

Version 3.2

Revision Date 04/13/2017

Print Date 07/03/2017

Precautionary statements : **Prevention:**
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ eye protection/ face protection.
Response:
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
Storage:
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.
P403 Store in a well-ventilated place.
Disposal:
Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

| Chemical name | CAS-No. | Concentration [%] |
|---|------------|-------------------|
| acetone | 67-64-1 | >= 50 - < 70 |
| Naphtha (petroleum), hydrotreated light | 64742-49-0 | >= 30 - < 50 |
| carbon dioxide | 124-38-9 | >= 5 - < 10 |
| heptane | 142-82-5 | >= 1 - < 5 |

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.
If unconscious place in recovery position and seek medical advice.

In case of skin contact : If skin irritation persists, call a physician.

SAFETY DATA SHEET

A00732 CAROLINA AUTO BRAKE & PARTS 20n14

Version 3.2

Revision Date 04/13/2017

Print Date 07/03/2017

- Wash off immediately with plenty of water for at least 15 minutes.
If on clothes, remove clothes.
- In case of eye contact : Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
If in eyes, rinse with water for 15 minutes.
- If swallowed : Keep respiratory tract clear.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
DO NOT induce vomiting unless directed to do so by a physician or poison control center.
- Most important symptoms and effects, both acute and delayed : Effects are immediate and delayed.
Symptoms may include irritation, redness, pain, and rash.
Symptoms of overexposure may include disorientation; dizziness; and confusion. May progress to unconsciousness, paralysis, and convulsions.
- Effects are dependent on exposure (dose, concentration, contact time).
Causes serious eye irritation.
May cause drowsiness or dizziness.
Review section 2 of SDS to see all potential hazards.
- Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon dioxide (CO₂)
Carbon monoxide
Smoke
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

SAFETY DATA SHEET
A00732 CAROLINA AUTO BRAKE & PARTS 20n14

Version 3.2

Revision Date 04/13/2017

Print Date 07/03/2017

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
 Ensure adequate ventilation.
 Remove all sources of ignition.
 Evacuate personnel to safe areas.
 Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.
 Prevent further leakage or spillage if safe to do so.
 If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.
 Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours or spray mist.
 Avoid exposure - obtain special instructions before use.
 Avoid contact with skin and eyes.
 For personal protection see section 8.
 Smoking, eating and drinking should be prohibited in the application area.
 Take precautionary measures against static discharges.
 Provide sufficient air exchange and/or exhaust in work rooms.
 Open drum carefully as content may be under pressure.
 Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
 No smoking.
 Keep in a dry, cool and well-ventilated place.
 Observe label precautions.
 Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type (Form of | Control parameters / | Basis |
|------------|---------|---------------------|----------------------|-------|
|------------|---------|---------------------|----------------------|-------|

SAFETY DATA SHEET

A00732 CAROLINA AUTO BRAKE & PARTS 20n14

Version 3.2

Revision Date 04/13/2017

Print Date 07/03/2017

| | | exposure) | Permissible concentration | |
|---------|----------------------------|----------------|---------------------------|-----------|
| acetone | 67-64-1 | TWA | 250 ppm | ACGIH |
| | | STEL | 500 ppm | ACGIH |
| | | TWA | 250 ppm 590 mg/m3 | NIOSH REL |
| | | TWA | 1,000 ppm 2,400 mg/m3 | OSHA Z-1 |
| | | TWA | 750 ppm 1,800 mg/m3 | OSHA P0 |
| | | STEL | 1,000 ppm 2,400 mg/m3 | OSHA P0 |
| | | STEL | 750 ppm 1,780 mg/m3 | CAL PEL |
| | | C | 3,000 ppm | CAL PEL |
| | | PEL | 500 ppm 1,200 mg/m3 | CAL PEL |
| | | carbon dioxide | 124-38-9 | TWA |
| STEL | 30,000 ppm | | | ACGIH |
| TWA | 5,000 ppm 9,000 mg/m3 | | | NIOSH REL |
| ST | 30,000 ppm 54,000 mg/m3 | | | NIOSH REL |
| TWA | 5,000 ppm 9,000 mg/m3 | | | OSHA Z-1 |
| TWA | 10,000 ppm 18,000 mg/m3 | | | OSHA P0 |
| STEL | 30,000 ppm 54,000 mg/m3 | | | OSHA P0 |
| PEL | 5,000 ppm 9,000 mg/m3 | | | CAL PEL |
| STEL | 30,000 ppm 54,000 mg/m3 | | | CAL PEL |
| heptane | 142-82-5 | | | TWA |
| | | C | 440 ppm 1,800 mg/m3 | NIOSH REL |
| | | TWA | 500 ppm 2,000 mg/m3 | OSHA Z-1 |
| | | TWA | 400 ppm 1,600 mg/m3 | OSHA P0 |
| | | STEL | 500 ppm 2,000 mg/m3 | OSHA P0 |
| | | PEL | 400 ppm 1,600 mg/m3 | CAL PEL |
| | | STEL | 500 ppm 2,000 mg/m3 | CAL PEL |
| | | STEL | 500 ppm 2,000 mg/m3 | CAL PEL |

Biological occupational exposure limits

| Component | CAS-No. | Control parameters | Biological specimen | Sampling time | Permissible concentration | Basis |
|-------------|---------|--------------------|---------------------|--|---------------------------|-----------|
| 2-PROPANONE | 67-64-1 | Acetone | Urine | End of shift (As soon as possible after exposure ceases) | 25 mg/l | ACGIH BEI |

SAFETY DATA SHEET**A00732 CAROLINA AUTO BRAKE & PARTS 20n14**

Version 3.2

Revision Date 04/13/2017

Print Date 07/03/2017

| | | | | | | |
|-------------|--|---------|-------|--|---------|-----------|
| 2-PROPANONE | | Acetone | Urine | End of shift (As soon as possible after exposure ceases) | 25 mg/l | ACGIH BEI |
|-------------|--|---------|-------|--|---------|-----------|

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection

: Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures

: When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a compressed gas

Colour : clear

Odour : solvent-like

Odour Threshold : No data available

pH : Not applicable

Melting point/freezing point : No data available

Boiling point : No data available

Flash point :
Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit : No data available

Lower explosion limit : No data available

SAFETY DATA SHEET

A00732 CAROLINA AUTO BRAKE & PARTS 20n14

Version 3.2

Revision Date 04/13/2017

Print Date 07/03/2017

| | |
|--|---------------------|
| Vapour pressure | : No data available |
| Density | : 0.728 g/cm3 |
| Solubility(ies) | |
| Water solubility | : No data available |
| Partition coefficient: n-octanol/water | : No data available |
| Auto-ignition temperature | : not determined |
| Thermal decomposition | : No data available |
| Viscosity | |
| Viscosity, kinematic | : No data available |
| Heat of combustion | : 35.20 kJ/g |

SECTION 10. STABILITY AND REACTIVITY

| | |
|------------------------------------|---|
| Reactivity | : Stable |
| Chemical stability | : Stable under normal conditions. |
| Possibility of hazardous reactions | : Vapours may form explosive mixture with air. No decomposition if stored and applied as directed. |
| Conditions to avoid | : Heat, flames and sparks. Extremes of temperature and direct sunlight. |
| Incompatible materials | : Strong oxidizing agents |
| Hazardous decomposition products | : Carbon oxides |

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

| | |
|------------------------------|--|
| Aggravated Medical Condition | : None known. |
| Symptoms of Overexposure | : Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. Symptoms of overexposure may include disorientation; dizziness; and confusion. May progress to unconsciousness, paralysis, and convulsions. Effects are dependent on exposure (dose, concentration, contact time). |

Carcinogenicity:

SAFETY DATA SHEET

A00732 CAROLINA AUTO BRAKE & PARTS 20n14

Version 3.2

Revision Date 04/13/2017

Print Date 07/03/2017

| | |
|--------------|--|
| IARC | No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC. |
| ACGIH | No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH. |
| OSHA | No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. |
| NTP | No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. |

Acute toxicity

Components:

acetone:

Acute oral toxicity : LD50 Rat: 5,800 mg/kg

Acute inhalation toxicity : LC50 Rat: 132 mg/l
Exposure time: 3 h

LC50 Rat: 50.1 mg/l

Acute dermal toxicity : LD50 Guinea pig: > 7,426 mg/kg

LD50 Rabbit: > 7,426 mg/kg

heptane:

Acute inhalation toxicity : LC50 Rat: 103 mg/l
Exposure time: 4 h

Skin corrosion/irritation

Product:

Remarks: May cause skin irritation in susceptible persons.

Serious eye damage/eye irritation

Product:

Remarks: Severe eye irritation

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

SAFETY DATA SHEET
A00732 CAROLINA AUTO BRAKE & PARTS 20n14

Version 3.2

Revision Date 04/13/2017

Print Date 07/03/2017

Reproductive toxicity

No data available

acetone:

Naphtha (petroleum), hydrotreated light:

carbon dioxide:

heptane:

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-
octanol/water : Remarks: No data available

Components:

heptane :

Partition coefficient: n-
octanol/water : log Pow: 5

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation

40 CFR Protection of Environment; Part 82 Protection of
Stratospheric Ozone - CAA Section 602 Class I
Substances

Remarks

This product neither contains, nor was manufactured

SAFETY DATA SHEET

A00732 CAROLINA AUTO BRAKE & PARTS 20n14

Version 3.2

Revision Date 04/13/2017

Print Date 07/03/2017

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of in accordance with local regulations.
- Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):
This material is not classified.

Transportation Regulation: IMDG (Vessel):
This material is not classified.

Transportation Regulation: IATA (Cargo Air):
This material is not classified.

Transportation Regulation: IATA (Passenger Air):
This material is not classified.

Transportation Regulation: TDG (Canada):
This material is not classified.

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.
No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

SAFETY DATA SHEET
A00732 CAROLINA AUTO BRAKE & PARTS 20n14

Version 3.2

Revision Date 04/13/2017

Print Date 07/03/2017

CERCLA Reportable Quantity

| Components | CAS-No. | Component RQ (lbs) | Calculated product RQ (lbs) |
|------------|---------|--------------------|-----------------------------|
| acetone | 67-64-1 | 5000 | * |

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard
 Sudden Release of Pressure Hazard
 Acute Health Hazard

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop 65

benzene : WARNING! This product contains a chemical known to the State of California to cause cancer. 71-43-2
 WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
 toluene : 108-88-3
 benzene : 71-43-2

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory
DSL : All components of this product are on the Canadian DSL

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

SAFETY DATA SHEET

A00732 CAROLINA AUTO BRAKE & PARTS 20n14


Version 3.2

Revision Date 04/13/2017

Print Date 07/03/2017

Further information

NFPA:




HMIS III:

| | |
|------------------------|----------|
| HEALTH | 2 |
| FLAMMABILITY | 4 |
| PHYSICAL HAZARD | 2 |

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

OSHA GHS Label Information:

Hazard pictograms :



Signal word :

Danger:

Hazard statements :

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness.

Precautionary statements :

Prevention: Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/ eye protection/ face protection.
Response: IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse.
Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place.
Disposal: Dispose of contents/container in accordance with local regulation.

| | |
|----------------|------------|
| Version: | 3.2 |
| Revision Date: | 04/13/2017 |
| Print Date: | 07/03/2017 |

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.