

# SAFETY DATA SHEET

Revision Date 18-May-2015

Version 2

## 1. IDENTIFICATION

### Product identifier

**Product Name** Acrylic Enamel Fleet White

### Other means of identification

**Product Code** PRO-AE12

**UN/ID no.** UN1263

**SKU(s)** PRO-AE12

### Recommended use of the chemical and restrictions on use

**Recommended Use** No information available.

**Uses advised against** No information available

### Details of the supplier of the safety data sheet

#### **Supplier Address**

Carolinas Auto Supply House

1020 Albany Place SE

Orange City, IA 51041

Phone: 712-737-4993

Fax: 712-737-4997

### Emergency telephone number

**Emergency Telephone** Chemtrec 1-800-424-9300

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Flammable liquids	Category 2

### **Emergency Overview**

#### **Danger**

#### **Hazard statements**

Harmful if inhaled

Causes skin irritation

May cause an allergic skin reaction

May cause genetic defects

May cause cancer

Causes damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

Highly flammable liquid and vapor



**Appearance** No information available

**Physical state** liquid

**Odor** No information available

**Precautionary Statements - Prevention**

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Use personal protective equipment as required
- Use only outdoors or in a well-ventilated area
- Wash face, hands and any exposed skin thoroughly after handling
- Contaminated work clothing should not be allowed out of the workplace
- Wear protective gloves
- Do not breathe dust/fume/gas/mist/vapors/spray
- Do not eat, drink or smoke when using this product
- Keep away from heat/sparks/open flames/hot surfaces. - No smoking
- Keep container tightly closed
- Ground/bond container and receiving equipment
- Use only non-sparking tools
- Take precautionary measures against static discharge
- Use explosion-proof electrical/ ventilating/ lighting/ equipment

**Precautionary Statements - Response**

- IF exposed or concerned: Get medical advice/attention
- IF skin irritation or rash occurs: Get medical advice/attention
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- Wash contaminated clothing before reuse
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
- Do NOT induce vomiting
- In case of fire: Use CO2, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

- Store locked up
- Store in a well-ventilated place. Keep cool

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

**Other Information**

- May be harmful if swallowed
- May be harmful in contact with skin
- Toxic to aquatic life with long lasting effects
- Toxic to aquatic life

Unknown acute toxicity                                 0% of the mixture consists of ingredient(s) of unknown toxicity

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS No.	Weight-%	Trade Secret
Xylene	1330-20-7	10 - 30	*
Titanium dioxide	13463-67-7	10 - 30	*
Barium sulfate	7727-43-7	3 - 7	*

Aromatic 100	64742-95-6	3 - 7	*
Ethyl Benzene	100-41-4	1 - 5	*
Solvent Naphtha, Medium Aliphatic	64742-88-7	1 - 5	*
Aliphatic Hydrocarbon	64742-49-0	1 - 5	*
1,2,4-Trimethylbenzene	95-63-6	1 - 5	*
Methyl Ethyl Ketoxime	96-29-7	0.1 - 1	*
Cumene	98-82-8	0.1 - 1	*
Stoddard Solvent	8052-41-3	0.1 - 1	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

##### Description of first aid measures

<b>General advice</b>	Immediate medical attention is required. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). If symptoms persist, call a physician.
<b>Eye contact</b>	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician. Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
<b>Skin Contact</b>	Wash off immediately with plenty of water. Call a physician immediately. Wash contaminated clothing before reuse. If skin irritation persists, call a physician. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
<b>Inhalation</b>	Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Call a physician immediately. Move to fresh air in case of accidental inhalation of vapors.
<b>Ingestion</b>	Do NOT induce vomiting. Rinse mouth. If symptoms persist, call a physician. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person. Clean mouth with water and drink afterwards plenty of water. Call a physician.
<b>Self-protection of the first aider</b>	Remove all sources of ignition. Use personal protective equipment as required.

##### Most important symptoms and effects, both acute and delayed

**Symptoms** No information available.

##### Indication of any immediate medical attention and special treatment needed

**Note to physicians** Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

##### Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable extinguishing media** CAUTION: Use of water spray when fighting fire may be inefficient.

##### Specific hazards arising from the chemical

Flammable.

##### Explosion data

**Sensitivity to Mechanical Impact** None.

**Sensitivity to Static Discharge** None.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined areas. Use personal protective equipment as required. Keep people away from and upwind of spill/leak.

**Environmental precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. See Section 12 for additional ecological information.

**Methods and material for containment and cleaning up**

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Pick up and transfer to properly labeled containers. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Cover liquid spill with sand, earth or other non-combustible absorbent material. Soak up with inert absorbent material.

**7. HANDLING AND STORAGE**

**Precautions for safe handling**

**Advice on safe handling** Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Avoid contact with skin, eyes or clothing. Use with local exhaust ventilation. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep containers tightly closed in a cool, well-ventilated place.

**Incompatible materials** Chlorinated compounds.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters**

**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m <sup>3</sup>	-
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 10 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup>

Barium sulfate 7727-43-7	TWA: 5 mg/m <sup>3</sup> inhalable fraction, particulate matter containing no asbestos and <1% crystalline silica	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 10 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
Ethyl Benzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>
1,2,4-Trimethylbenzene 95-63-6	-	-	TWA: 25 ppm TWA: 125 mg/m <sup>3</sup>
Cumene 98-82-8	TWA: 50 ppm	TWA: 50 ppm TWA: 245 mg/m <sup>3</sup> (vacated) TWA: 50 ppm (vacated) TWA: 245 mg/m <sup>3</sup> (vacated) S* S*	IDLH: 900 ppm TWA: 50 ppm TWA: 245 mg/m <sup>3</sup>
Stoddard Solvent 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m <sup>3</sup>	IDLH: 20000 mg/m <sup>3</sup> Ceiling: 1800 mg/m <sup>3</sup> 15 min TWA: 350 mg/m <sup>3</sup>

NIOSH IDLH *Immediately Dangerous to Life or Health*

**Other Information** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

**Appropriate engineering controls**

**Engineering Controls** Showers  
Eyewash stations  
Ventilation systems.

**Individual protection measures, such as personal protective equipment**

- Eye/face protection** Tight sealing safety goggles. Face protection shield.
- Skin and body protection** No special technical protective measures are necessary.
- Respiratory protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**General Hygiene Considerations** When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	No information available
<b>Appearance</b>	No information available	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point/freezing point	No information available	
Boiling point / boiling range	>= 89 °C / 192 °F	
Flash point	20 °C / 68 °F	
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	

**Flammability Limit in Air**

Upper flammability limit:	No information available
Lower flammability limit:	No information available
Vapor pressure	No information available
Vapor density	No information available
Specific Gravity	1.19
Water solubility	No information available
Solubility in other solvents	No information available
Partition coefficient	No information available
Autoignition temperature	No information available
Decomposition temperature	No information available
Kinematic viscosity	No information available
Dynamic viscosity	No information available
Explosive properties	No information available
Oxidizing properties	No information available

**Other Information**

Softening point	No information available
Molecular weight	No information available
VOC Content (%)	No information available
Density	9.91 lbs/gal
Bulk density	No information available
Percent solids by weight	58.6%
Percent volatile by weight	41.4%
Percent solids by volume	41.6%
Actual VOC (lbs/gal)	4.1
Actual VOC (grams/liter)	491.4
EPA VOC (lbs/gal)	4.1
EPA VOC (grams/liter)	491.4
EPA VOC (lb/gal solids)	9.9

<b>10. STABILITY AND REACTIVITY</b>
-------------------------------------

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of Hazardous Reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Chlorinated compounds.

**Hazardous Decomposition Products**

Carbon oxides.

<b>11. TOXICOLOGICAL INFORMATION</b>
--------------------------------------

**Information on likely routes of exposure**

<b>Product Information</b>	No data available
<b>Inhalation</b>	No data available.
<b>Eye contact</b>	No data available.

**Skin Contact** No data available.

**Ingestion** No data available.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Xylene 1330-20-7	= 3500 mg/kg ( Rat )	> 1700 mg/kg ( Rabbit ) > 4350 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h = 5000 ppm ( Rat ) 4 h
Titanium dioxide 13463-67-7	> 10000 mg/kg ( Rat )	-	-
Aromatic 100 64742-95-6	= 8400 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	= 3400 ppm ( Rat ) 4 h
Ethyl Benzene 100-41-4	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.2 mg/L ( Rat ) 4 h
Solvent Naphtha, Medium Aliphatic 64742-88-7	> 5000 mg/kg ( Rat )	= 3000 mg/kg ( Rabbit )	> 5.28 mg/L ( Rat ) 4 h
Aliphatic Hydrocarbon 64742-49-0	> 5000 mg/kg ( Rat )	> 3160 mg/kg ( Rabbit )	= 73680 ppm ( Rat ) 4 h
1,2,4-Trimethylbenzene 95-63-6	= 3280 mg/kg ( Rat )	> 3160 mg/kg ( Rabbit )	= 18 g/m <sup>3</sup> ( Rat ) 4 h
Methyl Ethyl Ketoxime 96-29-7	= 930 mg/kg ( Rat )	= 0.2 mg/kg ( Rabbit )	= 20 mg/L ( Rat ) 4 h
Cumene 98-82-8	= 1400 mg/kg ( Rat )	= 12300 µL/kg ( Rabbit )	= 39000 mg/m <sup>3</sup> ( Rat ) 4 h > 3577 ppm ( Rat ) 6 h

**Information on toxicological effects**

**Symptoms** No information available.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** No information available.

**Germ cell mutagenicity** No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Xylene 1330-20-7	-	Group 3	-	-
Titanium dioxide 13463-67-7	-	Group 2B	-	X
Ethyl Benzene 100-41-4	A3	Group 2B	-	X
Cumene 98-82-8	-	Group 2B	Reasonably Anticipated	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not classifiable as a human carcinogen

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

**Reproductive toxicity** No information available.

**STOT - single exposure** No information available.

**STOT - repeated exposure** No information available.

**Chronic toxicity** Ethylbenzene has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B). Prolonged or repeated overexposure to ethylbenzene may result in adverse effects to the kidneys, liver, respiratory system, thyroid, testicles, and pituitary glands. Avoid repeated exposure. May cause adverse effects on the bone marrow and blood-forming system.

**Target Organ Effects** blood, Central nervous system, Eyes, lungs, Respiratory system, Skin.

**Aspiration hazard** No information available.

**Numerical measures of toxicity - Product Information**

The following values are calculated based on chapter 3.1 of the GHS document mg/kg mg/l

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Toxic to aquatic life with long lasting effects

60.47% of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Xylene 1330-20-7	-	13.4: 96 h Pimephales promelas mg/L LC50 flow-through 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 19: 96 h Lepomis macrochirus mg/L LC50 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 780: 96 h Cyprinus carpio mg/L LC50 semi-static 780: 96 h Cyprinus carpio mg/L LC50 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static	3.82: 48 h water flea mg/L EC50 0.6: 48 h Gammarus lacustris mg/L LC50
Aromatic 100 64742-95-6	-	9.22: 96 h Oncorhynchus mykiss mg/L LC50	6.14: 48 h Daphnia magna mg/L EC50
Ethyl Benzene 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 32: 96 h Lepomis macrochirus mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 9.6: 96 h Poecilia reticulata mg/L LC50 static	1.8 - 2.4: 48 h Daphnia magna mg/L EC50
Solvent Naphtha, Medium Aliphatic 64742-88-7	450: 96 h Pseudokirchneriella subcapitata mg/L EC50	800: 96 h Pimephales promelas mg/L LC50 static	100: 48 h Daphnia magna mg/L EC50
Aliphatic Hydrocarbon 64742-49-0	-	-	2.6: 96 h Chaetogammarus marinus mg/L LC50
1,2,4-Trimethylbenzene 95-63-6	-	7.19 - 8.28: 96 h Pimephales promelas mg/L LC50 flow-through	6.14: 48 h Daphnia magna mg/L EC50
Methyl Ethyl Ketoxime 96-29-7	83: 72 h Desmodosmus subspicatus mg/L EC50	777 - 914: 96 h Pimephales promelas mg/L LC50 flow-through 760: 96 h Poecilia reticulata mg/L LC50 static 320 - 1000: 96 h Leuciscus idus mg/L LC50 static	750: 48 h Daphnia magna mg/L EC50
Cumene 98-82-8	2.6: 72 h Pseudokirchneriella subcapitata mg/L EC50	6.04 - 6.61: 96 h Pimephales promelas mg/L LC50 flow-through 4.8: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 2.7: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 5.1: 96 h Poecilia reticulata mg/L LC50 semi-static	0.6: 48 h Daphnia magna mg/L EC50 7.9 - 14.1: 48 h Daphnia magna mg/L EC50 Static

### Persistence and degradability

No information available.

### Bioaccumulation

No information available.

Chemical Name	Partition coefficient
Xylene 1330-20-7	2.77 - 3.15
Ethyl Benzene 100-41-4	3.118



1,2,4-Trimethylbenzene 95-63-6	3.63
Methyl Ethyl Ketoxime 96-29-7	0.65
Cumene 98-82-8	3.55

**Other adverse effects** No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Disposal of wastes** This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

**Contaminated packaging** Do not reuse container.

**US EPA Waste Number** D001 U055 U239 U404

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene 1330-20-7	-	Included in waste stream: F039	-	U239
Ethyl Benzene 100-41-4	-	Included in waste stream: F039	-	-
Cumene 98-82-8	-	-	-	U055

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Xylene 1330-20-7	Toxic Ignitable
Ethyl Benzene 100-41-4	Toxic Ignitable
Cumene 98-82-8	Toxic Ignitable

**14. TRANSPORT INFORMATION**

**DOT**

**UN/ID no.** UN1263  
**Proper shipping name** Paint  
**Subsidiary class** 3  
**Packing Group** II  
**Special Provisions** 149, B52, IB2, T4, TP1, TP8, TP28  
**Description** UN1263, Paint, (3), II  
**Emergency Response Guide Number** 128

**TDG**

**UN/ID no.** UN1263  
**Proper shipping name** Paint  
**Hazard Class** 3  
**Packing Group** II  
**Description** UN1263, Paint, 3, II

**MEX**

**UN/ID no.** UN1263  
**Proper shipping name** Paint  
**Hazard Class** 3

**Packing Group** II  
**Description** UN1263, Paint, 3, II

**ICAO (air)**

**UN/ID no.** UN1263  
**Proper shipping name** Paint  
**Hazard Class** 3  
**Packing Group** II  
**Special Provisions** A3, A72  
**Description** UN1263, Paint, 3, II

**IATA**

**UN/ID no.** UN1263  
**Proper shipping name** Paint  
**Hazard Class** 3  
**Packing Group** II  
**ERG Code** 3L  
**Special Provisions** A3, A72  
**Description** UN1263, Paint, 3, II

**IMDG**

**UN/ID no.** UN1263  
**Proper shipping name** Paint  
**Hazard Class** 3  
**Packing Group** II  
**EmS-No.** F-E, S-E  
**Special Provisions** 163  
**Description** UN1263, Paint, 3, II

**RID**

**UN/ID no.** UN1263  
**Proper shipping name** Paint  
**Hazard Class** 3  
**Packing Group** II  
**Classification code** F1  
**Description** UN1263, Paint, 3, II

**ADR**

**UN/ID no.** UN1263  
**Proper shipping name** Paint  
**Hazard Class** 3  
**Packing Group** II  
**Classification code** F1  
**Tunnel restriction code** (D/E)  
**Special Provisions** 163, 640C, 650  
**Description** UN1263, Paint, 3, II, (D/E)  
**Labels** 3

**ADN**

**Proper shipping name** Paint  
**Hazard Class** 3  
**Packing Group** II  
**Classification code** F1  
**Special Provisions** 163, 640C, 650  
**Description** UN1263, Paint, 3, II  
**Hazard label(s)** 3  
**Limited quantity (LQ)** 5 L  
**Ventilation** VE01

**15. REGULATORY INFORMATION**

**International Inventories**

**TSCA** Complies

<b>DSL/NDSL</b>	Complies *
<b>EINECS/ELINCS</b>	Complies *
<b>ENCS</b>	Does not comply *
<b>IECSC</b>	Complies *
<b>KECL</b>	Complies *
<b>PICCS</b>	Does not comply *
<b>AICS</b>	Does not comply *

\* This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

**Legend:**

- TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory
- DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List
- EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
- ENCS** - Japan Existing and New Chemical Substances
- IECSC** - China Inventory of Existing Chemical Substances
- KECL** - Korean Existing and Evaluated Chemical Substances
- PICCS** - Philippines Inventory of Chemicals and Chemical Substances
- AICS** - Australian Inventory of Chemical Substances

**US Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Xylene - 1330-20-7	1.0
Ethyl Benzene - 100-41-4	0.1
1,2,4-Trimethylbenzene - 95-63-6	1.0

**SARA 311/312 Hazard Categories**

<b>Acute health hazard</b>	Yes
<b>Chronic Health Hazard</b>	Yes
<b>Fire hazard</b>	Yes
<b>Sudden release of pressure hazard</b>	No
<b>Reactive Hazard</b>	No

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene 1330-20-7	100 lb	-	-	X
Ethyl Benzene 100-41-4	1000 lb	X	X	X

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Xylene 1330-20-7	100 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ
Ethyl Benzene 100-41-4	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ
Cumene 98-82-8	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Titanium dioxide - 13463-67-7	Carcinogen
Ethyl Benzene - 100-41-4	Carcinogen
Cumene - 98-82-8	Carcinogen
Crystalline Silica - 14808-60-7	Carcinogen

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Xylene 1330-20-7	X	X	X
Titanium dioxide 13463-67-7	X	X	X
Barium sulfate 7727-43-7	X	X	X
Ethyl Benzene 100-41-4	X	X	X
Solvent Naphtha, Medium Aliphatic 64742-88-7	X	-	-
1,2,4-Trimethylbenzene 95-63-6	X	X	X
Butyl Acetate 123-86-4	X	X	X
Triethylamine 121-44-8	X	X	X
Cumene 98-82-8	X	X	X
Cobalt neodecanoate 27253-31-2	X	-	X
Diethylene Glycol Ethyl Ether 111-90-0	X	-	X
Crystalline Silica 14808-60-7	X	X	X

**U.S. EPA Label Information**

**EPA Pesticide Registration Number** Not applicable

**Hazardous air pollutants (HAPS) content**

LIST OF HAZARDOUS AIR POLLUTANTS SUBJECT TO THE PROVISIONS OF THE CLEAN AIR ACT, TITLE I SECTION 112 'National Emission Standards for Hazardous Air Pollutants':

Chemical Name	Weight % of HAPS in Product	Pounds HAPS / Gal Product
Xylene 1330-20-7	21.98%	2.18
Ethyl Benzene 100-41-4	4.85%	0.48

**16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION**

**NFPA**                      **Health hazards** 2                      **Flammability** 3                      **Instability** 0                      **Physical and Chemical Properties** -  
**HMIS**                      **Health hazards** 2 \*                      **Flammability** 3                      **Physical hazards** 0                      **Personal protection** X

*Chronic Hazard Star Legend*                      \* = *Chronic Health Hazard*

**Revision Date**                      18-May-2015

**Revision Note**  
No information available

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

**End of Safety Data Sheet**