

MATERIAL SAFETY DATA SHEET

PAGE 1

PRODUCT CODE: HB-1689

PRODUCT NAME: BASECOAT CONVERTER

=====SECTION I - COMPANY IDENTIFICATION =====

COMPANY NAME *Carolinas Auto Supply House, Inc.*
ADDRESS *2135 Tipton Drive*
 Charlotte, NC 28206

INFORMATION PHONE : 800-438-4070
EMERGENCY PHONE : 800-424-9300

=====SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION=====

EXPORTABLE COMPONENTS	CAS #	VAPOR PRESSURE mm Hg @ TEMP		WEIGHT PERCENT
XYLENE OSHA PEL: 100 ppm ACGIH TLV: 435Mg/M ³	1330-20-7	14	100F	30-35
METHYL ISOBUTYL KETONE OSHA PEL: 50 ppm ACGIH TLV: 50 ppm	108-10-1	16	68F	10-15
ETHYL BENZENE OSHA PEL: 100 ppm	100-41-4	2	77F	<5
n-BUTYL ACETATE OSHA PEL: 150 ppm ACGIH TLV: 710 Mg/M ³	123-86-4	10	68F	1-5
TOLUENE OSHA PEL: 100 ppm ACGIH TLV: 377 Mg/M ³	108-88-3	36	86F	30-35

Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372. NOTE: Dry film may present a hazard if sanded or abraded in the form of a nuisance particle.
ACGIH TLV: 10 MG/M3

IMMEDIATE MEDICAL ATTENTION.
EYE CONTACT- FLUSH WITH LARGE QUANTITIES OF WATER FOR 15 MINUTES.

PAGE 3

SKIN CONTACT- WASH THOROUGHLY WITH SOAP AND WATER AND SEE A DOCTOR.
INGESTION- DO NOT INDUCE VOMITING, CAN CAUSE CHEMICAL PNEUMONITIS AND
PULMONARU EDEMA. CONTACT PHYSICIAN IMMEDIATELY.

=====SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE=====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: VENTILATE SPILL
AREA. ELIMINATE ALL SOURCES OF IGNITION. CONFINE SPILL AS QUICKLY AS POSSIBLE.
ABSORB WITH OIL ABSORBING COMPOUND, AND SCOOP UP FOR DISPOSAL.

WASTE DISPOSAL METHOD: TO MEET FEDERAL, STATE, OR LOCAL ENVIRONMENTAL
REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: KEEP CONTAINERS CLOSED
WHEN NOT IN USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME AND/OR
STRONG OXODANTS. TO REDUCE FIRE OR EXPLOSION RISK FROM STATIC
ACCUMULATION DISCHARGE, EFFECTIVELY GROUND PRODUCT TRANSFER SYSTEM IN
ACCORDANCE WITH NFPA STANDARD FOR PETROLEUM PRODUCTS.

OTHER PRECAUTIONS: N/A

=====SECTION VIII - CONTROL MEASURES=====

RESPIRATORY PROTECTION: A POSITIVE PRESSURE SUPPLIED AIR RESPIRATOR IS
MANDATORY. OBSERVE OSHA REGULATIONS FOR RESPIRATOR USE (29 CFR 1910.134).

VENTILATION: TO MEET FEDERAL, STATE, OR LOCAL ENVIRONMENTAL REGULATIONS.
LOCAL EXHAUST: OVER 60 FPM RECOMMENDED.

PROTECTIVE GLOVES: NEOPRENE, COMPLIANCE: CFR-170-179

EYE PROTECTION: SAFETY GLASSES, COMPLIANCE: ANSI Z87.1-1989, CSA Z94.3-M88

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: LEATHER BOOTS, COMPLIANCE:
ANSI Z41 PT 91 MI/75 C/75

WORK/HYGIENIC PRACTICES: AVOID PROLONGED OR REPEATED CONTACT IN ANY
FORM. THOROUGHLY CLEAN, DRY, AND/OR WASH ANY CONTAMINATED WORKING
APPAREL BEFORE REUSE. CLEANSE ANY CONTACTED SKIN AREAS THOROUGHLY AT THE
END OF EACH WORK PERIOD, ALSO BEFORE BREAKS AND MEALS. USE NECESSARY
PROTECTIVE EQUIPMENT AND MAINTAIN UPKEEP FOR EFFECTIVENESS.

=====SECTION IX - DISCLAIMER=====

THE COMPONENTS OF THIS PRODUCT ARE LISTED ON THE EPA/TSCA INVENTORY OF
CHEMICAL SUBSTANCES. TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION
CONTAINED HEREIN IS ACCURATE AND OBTAINED FROM SOURCES BELIEVED BY
CAROLINAS AUTO SUPPLY HOUSE, INC., TO BE ACCURATE.